



BIRCH, STEWART, KOLASCH & BIRCH, LLP

INTELLECTUAL PROPERTY LAW

8110 GATEHOUSE ROAD

SUITE 500 EAST

FALLS CHURCH, VA 22042-1210

USA

(703) 205-8000

FAX. (703) 205-8050

(703) 698-8590 (G IV)

e-mail: mailroom@bskb.com

web: http://www.bskb.com

CALIFORNIA OFFICE

650 TOWN CENTER DRIVE

SUITE 1120

COSTA MESA, CA 92626-7125

(714) 708-8555

FAX: (714) 708-8565

GARY D. YACURA
THOMAS S. AUCHTERLOFF
MICHAEL R. CAMMARATA
JAMES T. ELLER, JR.
SCOTT L. LOWE
MARY ANN CAPRIA
MARK J. NUEL, PH.D.
ROBERT V. RACUNAS
DARIN E. BARTHOLOMEW*
D. RICHARD ANDERSON
PAUL C. LEWIS
W. KARL RENNER

REG. PATENT AGENTS
FREDERICK R. HANDREN
ANDREW J. TELESZ, JR.
MARYANNE LIOTTA, PH.D.
MAKI HATSUMI
MIKE S. RYU
CRAIG A. McROBBIE
GARTH M. DAHLEN, PH.D.
LAURA C. LUTZ
ROBERT E. GOOZNER, PH.D.
HYUNG N. SOHN
MATTHEW J. LATTIG
ALAN PEDERSEN-GILES



TERRELL C. BIRCH
RAYMOND C. STEWART
JOSEPH A. KOLASCH
JAMES M. SLATTERY
BERNARD L. SWEENEY*
MICHAEL K. MUTTER
CHARLES GORENSTEIN
GERALD M. MURPHY, JR.
LEONARD R. SVENSSON
TERRY L. CLARK
ANDREW D. MEIKLE
MARC S. WEINER
JOE MCKINNEY MUNCY
ROBERT J. KENNEY
JOSEPH FARACI
DONALD J. DALEY
JOHN W. BAILEY
JOHN A. CASTELLANO, III

OF COUNSEL:
HERBERT M. BIRCH (1905-1996)
ELLIOT A. GOLDBERG*
WILLIAM L. GATES*
EDWARD H. VALANCE
RUPERT J. BRADY (RET.)*

*ADMITTED TO A BAR OTHER THAN VA

Date: August 5, 1999

Docket No.: 0950-0110P

Assistant Commissioner for Patents
Box PATENT APPLICATION
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of

Inventor(s): YAMAGUCHI, Fumihiko
MORITA, Masamichi; NAKAMAE, Yasushi
YANO, Hiroko; SATOH, Kazuyuki
IOKI, Masato

For: CARPET, STAINPROOFING AGENT FOR CARPET AND METHOD FOR
TREATING THE CARPET

Enclosed are:

- ☒ A specification consisting of 29 pages
☐ sheet(s) of _____ drawings
☒ An assignment of the invention
☒ Certified copy of Priority Document(s)
☒ Executed Declaration ☒ Original ☐ Photocopy
☐ A verified statement to establish small entity status under 37
CFR 1.9 and 37 CFR 1.27
☐ Preliminary Amendment
☐ Information Disclosure Statement, PTO-1449 and reference(s)

Specification

CARPET, STAINPROOFING AGENT FOR CARPET
AND METHOD FOR TREATING THE CARPET

Field of the Invention

5 The invention relates to a stainproofing agent
for carpet, a method for stainproofing a carpet and
stainproof-treated carpet.

Background Art

10 A variety of stainproofing agents are proposed
to impart water-repellency, oil-repellency and stainproof
properties to textile (eg. carpet).

 Japanese Examined Patent Publication No.
8606/1973 discloses that stainproof properties are
imparted by treating fibers with a homopolymer obtained
15 by polymerizing an ester of an unsaturated carboxylic
acid having a perfluoroalkyl group at both ends.
However, this homopolymer is insufficient in stainproof
properties.

 Japanese Examined Patent Publication No.
20 3767/1976 discloses that stainproof properties are
imparted to fibers by treating the fibers with a polymer
obtained by polymerizing (i) an ester of maleic or

fumaric acid having a perfluoroalkyl group at one end and
an aliphatic or aromatic group having no fluorine atom at
the other end with (ii) the other polymerizable
unsaturated compound. Since one end of the ester of
5 maleic or fumaric acid has no fluorine atom, its
polymerizablity is good. However, this polymer is
insufficient in water- and oil-repellency and is also
insufficient in stainproof properties.

U.S. Pat. No. 3,594,353 discloses that a water
10 repellency and stainproof properties to oil are imparted
to fibers by treating the fibers with a polymer obtained
by homopolymerizing an ester of itaconic acid having a
perfluoroalkyl group at both ends or one end or
copolymerizing said ester with the other polymerizable
15 unsaturated compound. However, this polymer is
insufficient in water- and oil-repellency and stainproof
properties.

None of stainproofing agents which have
hitherto been proposed presently has sufficient water-
20 and oil-repellency, stainproof properties and also
cleaning durability.

Although a carpet treated by a conventional

method to impart water-repellency, oil-repellency and stainproof properties thereto is better than untreated carpet in initial water-repellency, oil-repellency and stainproof properties, the properties are insufficient, and cleaning durability of the carpet is also insufficient.

It is an object of the invention to provide a carpet with excellent initial water-repellency and stainproof properties and also outstanding cleaning durability, a stainproofing agent for carpet, a method for stainproof treatment of carpet.

Disclosure of the invention

The inventors conducted extensive research to solve such problems and found that excellent water-repellency, stainproof properties and cleaning durability may be imparted to a carpet by treating the carpet with a stainproofing agent and a specific crosslinking agent, thus the invention has been accomplished.

Thus, the invention relates to a carpet to which stainproof properties and cleaning durability are imparted by treating the carpet with (i) a fluoroalkyl-containing compound and (ii) a triazine ring-containing

crosslinking agent, a stainproofing agent and
a method for stainproof treatment of a carpet.

Stainproof degree of carpet of the invention
maintains at least 30 % after cleaning of 3 times,
5 preferably 5 times, more preferably 10 times, further
preferably 15 times, in particular 20 times.

The fluorine-containing stainproofing agent
comprising a fluoroalkyl group (hereinafter referred to
as "Rf") containing compound is not specifically limited
10 to, but includes known compounds.

Examples of the fluorine-containing
stainproofing agent comprising Rf group-containing
compound are:

UNIDYNE TG-3010, TG-3020, TG-3040, TG-3510, TG-3520, TG-
15 3710, TG-3720, TG-3711, TG-452, TG-452A, TG-930, TG-232
(DAIKIN Industries Ltd.);

SCOTCHGUARD FX-1367F, FX-1373M, FX-1355, FC-393, FC-367,
FC-369, FC-398, FC-399 (Minnesota Mining and
Manufacturing Co.);


20 ZONYL FCC, 8779, AFC, NRD-372, N-140, N-119 (E.I. du Pont
de Nemours and Company);

ASAHIGUARD AG-820, AG-850, AG-923 (ASAHI GLASS CO.,


CRS-7 (NIKKA KAGAKU) .


5

(1) Fluoroalkyl-containing maleic acid diester copolymer



10






wherein Rf represents C_nH_{2n+1} (n is an integer of 5 to 21).

The amount of fluorine atom in solid content of stainproofing agent preferably ranges from 50 to 10,000 ppm based on the unit weight of carpet pile. Less than 50 ppm of the amount of fluorine atom results in insufficient stainproof properties. More than 10,000 of the amount of fluorine atom does not greatly improve stainproof properties.

The triazine ring-containing compound of the invention represented by formula (1) improves an adhesion property between said fluorine-containing stainproofing agent comprising Rf-containing compound and carpet pile, and also hardens coating:



wherein R^1 to R^6 are the same or different, and represent -H, -OH, $-\text{CH}_2\text{OCH}_3$, $-\text{CH}_2\text{OH}$, $-\text{CH}_2\text{CH}_2\text{OH}$, $-\text{CH}_2\text{CH}_2\text{CH}_2\text{OH}$, or $-\text{CH}_2\text{OC}_2\text{H}_5$, preferably $-\text{CH}_2\text{OH}$.

As crosslinking agent represented by formula
5 (1), trimethylolmelamine and hexamethylolmelamine are particularly preferable. Example of commercial name of the crosslinking agent is SUMITEX RESIN M-3 (trimethylolmelamine; SUMITOMO CHEMICAL Co. LTD.).

Coating mass of the triazine ring-containing
10 compound preferably ranges from 0.01 to 1.0 % by weight based on the unit weight of carpet. When coating mass is less than 0.01 % by weight, cleaning durability is insufficient. When coating mass is more than 1.0 % by weight, cleaning durability is not improved but results

in hard feeling, thereby not preferable.

Catalyst is preferably added to the triazine ring-containing compound to accelerate a reaction.

Examples of catalyst are formic acid, acetic acid and
5 like organic carboxylic acids; organic carboxylates
between the organic carboxylic acids and ammonium,
sodium, potassium, etc.; sulfuric acid, persulfuric acid,
hydrochloric acid, phosphoric acid, nitric acid and like
inorganic acids; inorganic acid salts between the
10 inorganic acids and ammonium, sodium, potassium,
magnesium, zinc, aluminum, iron, etc. The amount of
catalyst is not specifically limited to, but usually 5-
100 % by weight based on the amount of triazine ring-
containing compound.

15 The stainproofing agent for carpet may be in
the form of aqueous dispersion or solution in a solvent.

The stainproofing agent of the present
invention can be applied by any method according to the
kind of the material to be treated. For example, there
20 can be used a method for applying the agent of the
invention on the surface of material to be treated, using
a known application procedure such as immersion, coating,

etc., followed by drying. Furthermore, the stainproofing agent of the present invention may further comprise additives and a crosslinking agent other than said crosslinking agent. For example, polymethyl methacrylate
5 /ethyl methacrylate (P-MMA/EMA) and like polymer, additives such as insect repellents, flame retardants, antistatic agents, dye fixing agents, wrinkle inhibitors, softeners and stain block agents which inhibit adhesion of acid dye may be appropriately added.

10 The material to be treated with the stainproofing agent of the present invention is preferably a textile, in particular, a carpet. Examples of the textile are animal-origin natural fibers such as cotton, hemp, wool, silk, etc.; synthetic fibers
15 such as polyamide (nylon), polyester, polyvinyl alcohol, polyacrylonitrile, polyvinyl chloride, polypropylene, etc.; semisynthetic fibers such as rayon, cellulose acetate, etc.; inorganic fibers such as glass fibers, carbon fibers, asbestos fibers, etc.; and a mixture of
20 these fibers. Preferable fibers are polyamide (nylon), polyester, polyvinyl alcohol, polyacrylonitrile, polyvinyl chloride, polypropylene and like synthetic

fibers, rayon, cellulose acetate and like semisynthetic
fibers or a mixture thereof. The textile may be in any
form such as a fiber, a yarn, a cloth and the like. When
a carpet is treated with the stainproofing agent of the
5 present invention, the carpet may be formed after
treating fibers or yarns with the stainproofing
agent. Alternatively, the formed carpet may be treated
with the stainproofing agent.

The carpet of the invention may be pre-treated
10 with stain block agent before stainproof treatment.
Examples of stain block agent are generally a
poly(meth)acrylic acid and a sulphonic acid-containing
phenol/formaldehyde condensation product, specifically
FX-668F (Minnesota Mining and Manufacturing Co.), SR-
15 300 (E.I. du Pont de Nemours and Company). The stain block
agent is preferably used in a sufficient amount which
allow 0.05-10 % by weight of active ingredient based on
the weight of carpet to be adhered on carpet. Stain
block agent may be applied according to a usual treatment
20 process such as hot air treatment, steam treatment,
boiled water treatment, etc.

The stainproofing agent of the invention may

further comprises PEG and/or a copolymer comprising
(1) at least one selected from polyoxyethylene chain-
containing acrylate and methacrylate; and
(2) at least one reactive monomer selected from glycerol
5 methacrylate and glycidyl methacrylate).

The copolymer or PEG may be used in an amount
of 1-50% by weight, preferably 2-20% by weight based on
the solid content of repellant.

Color of carpet to be treated includes blue.

10 With respect to color of carpet,
L = 40 to 80, preferably L = 40 to 60;
a = +0.1 to -0.8, preferably a = -0.1 to -0.6;
b = -13 to -25, preferably b = -17 to -21.

The carpet of the invention maintains a
15 stainproof degree during resoiling of at least 20%,
preferably at least 30% after one cycle of contamination,
cleaning and recontamination.

Best Mode for Carrying out the Invention

The invention is described below in detail by
20 way of example. However, the invention is in no way
limited to the examples.

Evaluation procedures of water-repellency, oil-

repellency and stainproof property, and cleaning process are shown below.

<Water-repellency>

Five drops of isopropanol/water mixture having the following composition are slowly placed on the surface of carpet textile. Water repellency is represented by a maximum score at which at least 4 drops maintain a liquid form (repellent) after 3 minutes.

Table 1

Score	Composition (% by volume)	
	Isopropanol	Water
0	0	100
2	2	98
5	5	95
10	10	90
15	15	85
20	20	80
25	25	75
30	30	70
40	40	60
50	50	50

<Oil-repellency>

According to AATCC-TM-118-1966, five drops of the following test solution are slowly placed on the surface of carpet. Penetration state of the drops are observed after 3 minutes. Oil-repellency is represented by a maximum score at which at least 4 drops show no penetration into carpet.

Table 2

Score	Test solution	Surface tension (mN/m: 25°C)
	0 Inferior to 1	
5	1 Nujol	31.2
	2 A mixture of N-hexadecane (35 parts by weight) and Nujol (65 parts by weight)	29.6
	3 n-hexadecane	27.3
10	4 n-tetradecane	26.7

<Stainproof property test 1>

Carpet treated with a stainproofing agent is evaluated according to AATCC-123-1995.

Carpet textile is cut into a 5.5cm x 8cm test piece. The test piece is allowed to stand in thermohygrostat (21°C, 65%RH) for 4 hours, dried sufficiently, followed by contaminated with a dry soil having the following composition. Specifically, five carpet test pieces are attached to a ball mill in such a manner that the stainproof surface of the carpet is in an upward direction. 0.031 g of dry soil per 1cm² surface area of the carpet test piece (corresponding to 6.82g in case of five carpet test pieces) and 50 ceramic balls (2.0 cm in diameter) are put in the ball mill. The ball mill is then rotated at 80 rpm for 7.5 minutes to give the carpet test piece on the surface of which the dry

soil is uniformly adhered. The ball mill has a tubular shape, and a base inner diameter of 12.0 cm and a height of 9.5 cm. The excessive dry soil on the carpet test piece is thoroughly removed by aspiration with domestic vacuum cleaner. Color difference (ΔE) on the surface of carpet is determined with color difference meter (MINOLTA CR-310). Stainproof ratio (%) is calculated on the basis of the following equation.

$$\text{Stainproof ratio (\%)} = 100 \times (\Delta E_N - \Delta E_{Tn}) / \Delta E_N$$

10 ΔE_N : Color difference after stainproof test of untreated carpet

ΔE_{Tn} : Color difference after stainproof test of carpet treated by the stainproofing agent

n : the number of cleaning

Dry soil composition, L, a and b values are shown below:

<u>Composition</u>	<u>Content (% by weight)</u>
--------------------	------------------------------

Peat moss	38.4
-----------	------

Cement	18
--------	----

5 Kaoline	18
-----------	----

Silica	18
--------	----

Carbon black	1.15
--------------	------

Iron oxide	0.3
------------	-----

<u>Nujol</u>	<u>6.25</u>
--------------	-------------

10 with respect to Lab values, L : 25-31, a : 2.3-2.6, b :
4.2-4.8.

<Stainproof property test 2>

<Stainproof property test 2> is evaluated in
the same manner as <Stainproof property test 1> except
15 that the size of carpet textile is 11cm x 8cm; and that
the amount of dry soil per 1cm² surface area of the
carpet test piece is 0.0062g (corresponding to 1.64g in
case of three carpet test pieces); and that rotation
conditions are 80 rpm for 5 min.

20 <Cleaning method>

Cleaning of the carpet textile treated with a

stainproofing agent is conducted according to AARCC-138.

Stated more specifically:

- (i) the surface of carpet test piece (11cm x 11cm) is washed with running water (50°C) for 1 min, followed by squeezed with mangle (pressure : 5mg/cm²).
- (ii) The carpet test piece is fixed and set on the testing stand of cleaning test machine (STAIN & CLEANING TESTER: YOSHIDA SEIKI SEISAKUSYO) as defined in JIS L1023-1992 in order that rotary brushes rub carpet piles.
- (iii) Cleaning of the carpet is carried out by pouring 4.1ml of 1 % sodium lauryl sulfate (SLS) aqueous solution (adjusted at pH 8 with NaOH aqueous solution) warmed to 50°C to carpet with pipette, followed by rotating rotary brush and testing stand.

One cleaning is composed of 5 rotations in regular direction, 5 rotations in reverse direction, further 5 rotations in regular direction and 5 rotations in reverse direction during which rotary brushes maintain rubbing carpet.

"Cleaning three times" mean that the process is repeated 3 times except that SLS 1% aqueous solution is not further added.

"Cleaning five times" means that the process is repeated 5 times except that SLS 1% aqueous solution is not added.

The number of revolutions of the testing stand is 20 rpm. The number of rotation of brush is 240 rpm. Vacuum and water jet nozzle of cleaning test machine are not used.

The carpet is thoroughly rinsed with running water (50°C), squeezed with mangle, and then dried in hot-air drying chamber at 105°C for 30 min leading to completion of cleaning.

Example 1

Nylon 6,6 carpet textile (cut pile, pile density: 40 oz/yd², pile height: 1/4 inch, color: light blue) was dipped in water, squeezed with mangle to adjust wet pickup (the increased weight, represented by % by weight, of carpet after dipping in comparison with initial weight of carpet test piece) at 20% by weight.

A Stainproofing agent composition as shown in table 4 was prepared by mixing and stirring 8 parts by weight of UNIDYNE TG-3010 (Rf group-containing stainproofing agent for carpet; DAIKIN INDUSTRIES LTD.),

1.9 parts by weight of SUMITECH RESIN M-3

(trimethylolmelamine: SUMITOMO CHEMICAL CO., LTD.), 0.6 part by weight of SUMITECH ACCELERATOR (ACX; catalyst for SUMITECH RESIN M-3 which is a product of SUMITOMO

5 CHEMICAL CO., LTD.) and 89.5 parts by weight of water.

The carpet test piece (20g) was treated with the stainproofing agent composition (1.5g; corresponding to 400ppm fluorine atom per 1g of carpet), followed by heat-treated with pin stenter at 130°C for 10 min.

10 The carpet test piece was cleaned (1 time, 3 times, 5 times) according to the above-defined method to evaluate water-repellency, oil-repellency and stainproof property before and after cleaning. The results are shown in table 6.

15 Examples 2-6


 Stainproofing agent compositions as shown in table 4 were prepared. The carpet test piece was treated in the same manner as example 1.

 The results are shown in table 6.

20 Example 7

 A stainproofing agent composition was prepared by diluting 6 parts by weight of emulsion (solid content

30 % by weight) comprising Rf-maleate/methylmethacrylate (MMA)=60/40 (weight ratio) copolymer, SUMITEX RESIN M-3 and SUMITEX ACCELERATOR (ACX) with 94 parts by weight of water. The carpet test piece was treated with the stainproofing agent composition thus obtained in the same manner as example 1.



wherein n is an integer of 3 to 8.

Examples 8-10

The carpet test piece shown in example 1 was subjected to stain block processing. To a stain block agent (FX-668F: Minnesota Mining and Manufacturing Co.) diluted to 0.7% with water was added MgSO_4 (1%), and pH of the solution was adjusted at 2 with sulfamic acid.

The carpet test piece was boiled in the solution for 5 minutes. The test piece was washed with running water to remove an excess stain block agent and dried at 130°C.

The resulting carpet test piece was dipped in water,
5 squeezed with mangle to adjust wet pickup thereof at 20%.

Stainproofing agents as shown in table 4 were prepared to treat the carpet test piece in the same manner as example 1. The results are shown in table 6.

A stain block agent is a treatment applied to a
10 material in order to inhibit adhesion of acid dye in the process of stainproof processing of carpet.

Comparative examples 1-4

Stainproofing agent mixtures shown in table 5 were prepared and used for treating the carpet test piece
15 in the same manner as example 1. The results are shown in table 6.

Table 4

Ex.	Rf-containing Stainproofing Agent	Crosslinking Agent	Water (Wt.part)	Other Additives
5	Kind/Amount (Wt. Part)	Kind/Amount (Wt. Part)		Kind/Amount (Wt. Part)
	1 UNIDYNE TG3010/8	SUMITEX RESIN M-3/1.8	89.5	ACX (0.6)
	2 UNIDYNE TG3010/8	SUMITEX RESIN M-3/0.9	89.8	ACX (0.3)
10	3 Rf-maleate-MMA Copolymer 30% Emulsion/5	SUMITEX RESIN M-3/0.9	93.8	ACX (0.3)
	4 SCOT GUARD FX-1373M/5	SUMITEX RESIN M-3/0.9	93.8	ACX (0.3)
15	5 SCOT GUARD FX-1367F/8	SUMITEX RESIN M-3/2.1	89.2	ACX (0.7)
	6 N-140/5	SUMITEX RESIN M-3/1.5	93	ACX (0.5)
20	8 UNIDYNE TG3010/8	SUMITEX RESIN M-3/1.8	89.8	ACX (0.3)
	9 Rf-maleate-MMA Copolymer 30% Emulsion/5	SUMITEX RESIN M-3/0.9	93.8	ACX (0.3)
25	10 SCOT GUARD FX-1367F/8	SUMITEX RESIN M-3/2.1	89.2	ACX (0.7)

Table 5

Comp. Ex.	Rf-containing Stainproofing Agent	Crosslinking Agent	Water (Wt.part)	Other Additives
5	Kind/Amount (Wt. Part)	Kind/Amount (Wt. Part)		Kind/Amount (Wt. Part)
1	UNIDYNE TG3010/8	- / -	89.5	-
2	Rf-maleate-MMA Copolymer 30% Emulsion/5	- / -	89.8	-
3	Rf-maleate-MMA Copolymer 30% Emulsion/5	ELASTRON BN-69/1.5	93.35	Cat64 (0.15)
4	SCOT GUARD FX-1367F/5	- / -	93.8	-

Table 6

	Water-Repellency (Score)	Oil-Repellency (Score)	Stainproof Ratio (%)
20	Number of Cleaning		
	0 1 3 5	0 1 3 5	0 1 3 5
Example 1	20 15 15 15	0 0 0 0	41 39 37 35
Example 2	20 15 10 10	0 0 0 0	41 38 35 33
Example 3	20 20 15 15	0 0 0 0	42 40 38 35
Example 4	20 20 15 15	0 0 0 0	40 39 38 36
Example 5	25 25 25 20	1 1 1 1	50 49 47 43
Example 6	25 20 20 15	0 0 0 0	52 50 48 45
Example 7	20 15 15 10	0 0 0 0	40 38 37 32
Example 8	25 15 15 10	0 0 0 0	55 54 51 49
Example 9	30 25 20 20	0 0 0 0	55 55 54 54
Example 10	30 25 20 20	1 1 1 1	55 55 54 54
Comp.Ex.1	20 0 x x	0 0 0 0	43 28 18 15
Comp.Ex.2	20 15 0 0	0 0 0 0	41 27 21 18
Comp.Ex.3	20 15 5 5	0 0 0 0	27 26 25 24
Comp.Ex.4	10 5 x x	1 1 1 0	33 28 22 15

In table 3, the number of cleaning "0" means

before cleaning.

With respect to stainproof ratio, carpet which is not treated with a stainproofing agent has a stainproof ratio of 100% before contamination and 0% after contamination.

Example 11

Stain block processing was carried out in advance in the same manner as examples 8-10.

A stainproofing agent composition was prepared by mixing 8 parts by weight of TG-3010, 0.9 part by weight of SUMITEX RESIN M-3, 0.3 part by weight of SUMITEX ACCELERATOR, 0.7 part by weight of polyethyleneglycolmethacrylate (PEGMA)/glycerol methacrylate (GMA)=70/30 (by weight ratio) copolymer and 90.1 parts by weight of water. The carpet test piece was treated by the composition in the same manner as example 1.

The test piece was subjected to a test cycle comprising <stainproof property 2>, cleaning and <stainproof property 2>. After the last <stainproof property 2> treatment, stainproof ratio of the test piece was determined. The results are shown in table 8.

Comparative example 5

Stain block processing was carried out in advance in the same manner as examples 8-10.

A stainproofing agent composition as shown in table 7 was prepared. The carpet test piece was treated with the stainproofing agent composition in the same manner as example 1. The test piece was subjected to the evaluation test as shown in example 11. The results are shown in table 8.

10

Table 7

	Rf- Containing Stain- proofing Agent	Cross- linking Agent	PEGMA/GMA Copolymer	Water (Wt.Part)	Other Additive
	Kind/Amount (Wt. Part)	Kind/Amount (Wt. Part)	(Wt. Part)		Kind/Amount (Wt. Part)
15	Ex.11 UNIDYNE TG3010/8	SUMITEX RESIN M-3/0.9	0.7	90.1	ACX (0.3)
20	Comp. UNIDYNE Ex.5 TG3010/8	- / -	- / -	92	- / -

Table 8

	Stainproof ratio (%)	
	Initial	Recontamination
25	Ex.11 65	35
	Comp. Ex.5 60	15

Claims

1. A carpet comprising a stainproof-treated textile, wherein the carpet has stainproof ratio as defined below of at least 30 %:

5 Stainproof ratio (%) = $100 \times (\Delta E_N - \Delta E_{Tn}) / \Delta E_N$

ΔE_N : Color difference after stainproof test of untreated carpet

ΔE_{Tn} : Color difference after stainproof test of carpet which is stainproof-treated

10 wherein n is the number of cleaning; cleaning is conducted according to AATCC-138, $n \leq 20$).

2. The carpet according to claim 1 wherein the carpet maintain stainproof ratio of at least 30 % after five times of cleaning.

15 3. The carpet according to claim 1 wherein a dry soil composition used in the stainproof test according to AATCC-123 is shown in the following table:

	<u>Composition</u>	<u>Content (% by weight)</u>
	Peat moss	38.4
20	Cement	18
	Kaoline	18
	Silica	18
	Carbon black	1.15
	Iron oxide	0.3
25	<u>Nujol</u>	<u>6.25</u>

4. The carpet according to claim 1 which is

treated with a stainproofing agent composition for carpet comprising:

- (1) a fluorine-containing stainproofing agent comprising a fluoroalkyl-containing compound; and
- 5 (2) a triazine ring-containing crosslinking agent.

5. The carpet according to claim 4 wherein the fluorine-containing stainproofing agent comprising a fluoroalkyl-containing compound comprises at least one selected from the group consisting of fluoroalkyl-
10 containing maleic acid diester copolymer, fluoroalkyl-containing adipic acid diester compound and fluoroalkyl-containing urethane compound.

6. A stainproofing agent composition for carpet comprising:

- 15 (1) a fluorine-containing stainproofing agent comprising a fluoroalkyl-containing compound; and
- (2) a triazine ring-containing crosslinking agent.

7. The stainproofing agent composition according to claim 6 wherein the fluorine-containing
20 stainproofing agent comprising a fluoroalkyl-containing compound comprises at least one selected from the group consisting of fluoroalkyl-containing maleic acid diester

copolymer, fluoroalkyl-containing adipic acid diester compound and fluoroalkyl-containing urethane compound.

8. A method for treating carpet with the stainproofing agent composition for carpet according to
5 claims 6.

9. The stainproofing agent composition for carpet according to claims 6 which further comprises at least one selected from the group consisting of PEG and a copolymer comprising:

- 10 (1) at least one monomer selected from the group consisting of acrylate and methacrylate which have a polyoxyethylene chain; and
(2) at least one reactive monomer selected from the group consistoing of glycerol methacrylate and glycidyl
15 methacrylate.

10. The carpet according to claim 1 treated with the stainproofing agent composition according to claim 9.

11. The method according to claim 8 wherein
20 the carpet is treated with the stainproofing agent composition according to claim 9.

12. The carpet according to claim 1 which is

10

5

ABSTRACT

The invention relates to a carpet comprising a stainproof-treated textile, wherein the carpet has stainproof ratio (%) of at least 30 % as defined below :

5 Stainproof ratio (%) = $100 \times (\Delta E_N - \Delta E_{Tn}) / \Delta E_N$

ΔE_N : Color difference after stainproof test of untreated carpet;

ΔE_{Tn} : Color difference after stainproof test of carpet which is stainproof-treated;

10 wherein n is the number of cleaning; cleaning is conducted according to AATCC-138, $n \leq 20$.

665049.0249.0305

PLEASE NOTE:
YOU MUST
COMPLETE THE
FOLLOWING:



Insert Title



Check Box If
Appropriate —
For Use Without
Specification
Attached



COMBINED DECLARATION AND POWER OF ATTORNEY FOR PATENT AND DESIGN APPLICATIONS

ATTORNEY DOCKET NO.

950-110P

As a below named inventor, I hereby declare that: my residence post office address and citizenship are as stated next to my name; that I verily believe that I am the original, first and sole inventor (if only one inventor is named below) or a joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: * CARPET, STAINPROOFING AGENT FOR CARPET AND METHOD
FOR TREATING THE CARPET

the specification of which is attached hereto unless one of the following boxes is checked:

- ☐ The Specification was filed on _____ and was assigned
Serial No. _____ and was amended on _____
☐ was filed as PCT international application number _____ on
_____ and was amended under PCT Article 19 on _____
(if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I do not know and do not believe the same was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof, or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months (six months for designs) prior to this application, and that no application for patent or inventor's certificate on this invention has been filed in any country foreign to the United States of America prior to this application by me or my legal representatives or assigns, except as follows:

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below:

Prior Foreign Application(s)	Priority	Claimed
<u>232084/1998</u> (Number)	<u>Japan</u> (Country)	<u>08/18/1998</u> (Month/Day/Year Filed)
<u>111737/1999</u> (Number)	<u>Japan</u> (Country)	<u>04/20/1999</u> (Month/Day/Year Filed)
_____ (Number)	_____ (Country)	_____ (Month/Day/Year Filed)
_____ (Number)	_____ (Country)	_____ (Month/Day/Year Filed)
_____ (Number)	_____ (Country)	_____ (Month/Day/Year Filed)

All Foreign Applications, if any, for any Patent or Inventor's Certificate Filed More Than 12 Months (6 Months for Designs) Prior To The Filing Date of This Application:

Country	Application No.	Date of Filing (Month/Day/Year)
_____	_____	_____
_____	_____	_____

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status — patented, pending, abandoned)
_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status — patented, pending, abandoned)

I hereby appoint the following attorneys to prosecute this application and/or an international application based on this application and to transact all business in the Patent and Trademark Office connected therewith and in connection with the resulting patent based on instructions received from the entity who first sent the application papers to the attorneys identified below, unless the inventor(s) or assignee provides said attorneys with a written notice to the contrary:

RAYMOND C. STEWART (Reg. No. 21,066)
JOSEPH A. KOLASCH (Reg. No. 22,463)
JAMES M. SLATTERY (Reg. No. 28,380)
DONALD C. KOLASCH (Reg. No. 23,038)
CHARLES GORENSTEIN (Reg. No. 29,271)
LEONARD R. SVENSSON (Reg. No. 30,330)

TERRELL C. BIRCH (Reg. No. 19,382)
ANTHONY L. BIRCH (Reg. No. 26,122)
BERNARD L. SWEENEY (Reg. No. 24,448)
MICHAEL K. MUTTER (Reg. No. 29,680)
GERALD M. MURPHY, JR. (Reg. No. 28,977)
TERRY L. CLARK (Reg. No. 32,644)

**PLEASE NOTE:
YOU MUST
COMPLETE THE
FOLLOWING:**

Send Correspondence to: **BIRCH, STEWART, KOLASCH AND BIRCH**
301 North Washington Street
P.O. Box 747
Falls Church, Virginia 22040-0747
Telephone: (703) 241-1300

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of First or Sole Inventor:
Insert Name of Inventor
Insert Date This Document Is Signed
Insert Residence
Insert Citizenship

**Insert Post Office
Address**

Full Name of Second Inventor, if any:
see above

Full Name of Third Inventor, if any:
see above

Full Name of Fourth Inventor, if any:
see above

Full Name of Fifth Inventor, if any:
see above

***Note:** Must be completed
— date this document is
signed.

Page 2 of 2
(USPTO Approved 3-90)
(Revised 3-92)

GIVEN NAME Fumihiko		FAMILY NAME YAMAGUCHI		INVENTOR'S SIGNATURE <i>Fumihiko Yamaguchi</i>		*DATE July 14, 1999	
RESIDENCE (City, State & Country) Settsu-shi, Osaka-fu, Japan					CITIZENSHIP Japan		
POST OFFICE ADDRESS (Complete Street Address including City, State & Country) c/o Yodogawa Seisakusho, DAIKIN INDUSTRIES, LTD., 1-1, Nishihitotsuya, Settsu-shi, Osaka-fu, Japan							
GIVEN NAME Masamichi		FAMILY NAME MORITA		INVENTOR'S SIGNATURE <i>Masamichi Morita</i>		*DATE July 14, 1999	
RESIDENCE (City, State & Country) Settsu-shi, Osaka-fu, Japan					CITIZENSHIP Japan		
POST OFFICE ADDRESS (Complete Street Address including City, State & Country) c/o Yodogawa Seisakusho, DAIKIN INDUSTRIES, LTD., 1-1, Nishihitotsuya, Settsu-shi, Osaka-fu, Japan							
GIVEN NAME Yasushi		FAMILY NAME NAKAMAE		INVENTOR'S SIGNATURE <i>Yasushi Nakamae</i>		*DATE July 14, 1999	
RESIDENCE (City, State & Country) Settsu-shi, Osaka-fu, Japan					CITIZENSHIP Japan		
POST OFFICE ADDRESS (Complete Street Address including City, State & Country) c/o Yodogawa Seisakusho, DAIKIN INDUSTRIES, LTD., 1-1, Nishihitotsuya, Settsu-shi, Osaka-fu, Japan							
GIVEN NAME Hiroko		FAMILY NAME YANO		INVENTOR'S SIGNATURE <i>Hiroko Yano</i>		*DATE July 14, 1999	
RESIDENCE (City, State & Country) Settsu-shi, Osaka-fu, Japan					CITIZENSHIP Japan		
POST OFFICE ADDRESS (Complete Street Address including City, State & Country) c/o Yodogawa Seisakusho, DAIKIN INDUSTRIES, LTD., 1-1, Nishihitotsuya, Settsu-shi, Osaka-fu, Japan							
GIVEN NAME Kazuyuki		FAMILY NAME SATOH		INVENTOR'S SIGNATURE <i>Kazuyuki Satoh</i>		*DATE July 14, 1999	
RESIDENCE (City, State & Country) Settsu-shi, Osaka-fu, Japan					CITIZENSHIP Japan		
POST OFFICE ADDRESS (Complete Street Address including City, State & Country) c/o Yodogawa Seisakusho, DAIKIN INDUSTRIES, LTD., 1-1, Nishihitotsuya, Settsu-shi, Osaka-fu, Japan							

Full Name of sixth
Inventor:
Insert Name of Inventor
Insert Date This
Document Is Signed
Insert Residence
Insert Citizenship

Insert Post Office
Address

Full Name of
Inventor, if any:
see above

Full Name of
Inventor, if any:
see above

Full Name of
Inventor, if any:
see above

Full Name of
Inventor, if any:
see above

Full Name of
Inventor, if any:
see above

Full Name of
Inventor, if any:
see above

Full Name of
Inventor, if any:
see above

GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE	*DATE
Masato	IOKI	Masato Ioki	July 14, 1999
RESIDENCE (City, State & Country)		CITIZENSHIP	
Settsu-shi, Osaka-fu, Japan		Japan	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
c/o Yodogawa Seisakusho, DAIKIN INDUSTRIES, LTD., 1-1, Nishihitotsuya, Settsu-shi, Osaka-fu, Japan			
GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE	*DATE
RESIDENCE (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE	*DATE
RESIDENCE (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE	*DATE
RESIDENCE (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE	*DATE
RESIDENCE (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE	*DATE
RESIDENCE (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE	*DATE
RESIDENCE (City, State & Country)		CITIZENSHIP	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			

*Note: Must be completed
— date this document is
signed.